

## Serie: MAQ2 M - TC

		M 11	M 14	M 18	M 25
<b>DRUM</b>					
Loading capacity ratio 1:10	Kg	10	13	18	25
Volume of the drum	Lt	100	130	180	250
Diameter of the drum	∅	620	620	620	700
Drum depth	mm	330	430	600	670
Washing speed	G/min	50	50	50	47
Extract speed	G/min	760	760	760	690
G Factor		200	200	200	200
Noise level	Db	60	60	60	60

### LOADING DOOR

High at the middle of the door	mm	570	570	655	700
Diameter of the loading door	∅	373	373	373	373

### ELECTRICAL POWER

Motor	Kw	0,75	1,5	2,2	3
Electrical heaters	Kw	6	9	12	18
Total power of electrical version	Kw	6,25	9,5	12,75	19
Total power of steam version	Kw	0,75	1,5	2,2	3
Total power hot WATER version	Kw	0,75	1,5	2,2	3

### CONNECTIONS

Water outlet	∅	3"	3"	3"	3"
Water inlet	∅	3/4"	3/4"	3/4"	3/4"
Water pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam inlet	∅	1/2"	1/2"	1/2"	3/4"

### DIMENSIONS OF THE MACHINE

front width	mm	719	719	788	884
Depth	mm	665	810	828	965
High	mm	1158	1158	1308	1318
Net weight	Kg	217	239	281	340

### DIMENSIONS WITH PACKAGE

Front width	mm	800	800	860	930
Depth	mm	990	990	1010	1150
High	mm	1350	1350	1500	1500
Gross weight	Kg	225	247	301	370
Volume	mt3	1,07	1,07	1,3	1,6