

Series: S - PSM

		S 210	S 330	S 460	S 550	S 660	S 900	S 1200	S 1500
DRUM									
Loading capacity ratio 1:20	Kg	10 ÷ 12	16 ÷ 18	23 ÷ 26	27 ÷ 31	33 ÷ 37	45 ÷ 50	60 ÷ 67	75 ÷ 83
Volume of the drum	Lt	210	330	460	550	660	896	1202	1500
Drum diameter	∅	750	750	855	947	947	1225	1225	1225
Drum depth	mm	475	746	800	780	780	760	1020	1252
Opening loading door	∅	574	574	574	802	802	802	802	802

POWER ELECTRICAL VERSION

Total power	Kw	12,85	18,85	25,17	31,35	37,35	57	75,35	75,75
Consumption	Amp	27	27	35	37	54	100	130	130

POWER GAS VERSION

Heating power	Kw	20,51	20,51	20,51	31	41	60	90	120
Installed electrical power	Kw	0,55	0,55	0,75	0,75	0,75	2,2	2,2	2,2
Consumption	Amp	4	4	4	6,3	6,3	10	10	10

POWER STEAM VERSION

Heating power	Kw	30	30	49,2	50,1	50,1	91,3	128	128
Installed electrical power	Kw	0,55	0,55	0,75	0,75	0,75	2,2	2,2	2,2
Consumption	Amp	4	4	4	6,3	6,3	10	10	10

MOTORS

Fan air flow	mt ³ /h	1200	1200	1500	1500	1500	4500	4500	4500
Fan power	Kw	0,55	0,55	0,75	0,75	0,75	2,2	2,2	2,2
Drum motor	Kw	0,25	0,25	0,37	0,55	0,55	0,75	1,1	1,5

CONNECTIONS

Air outlet	∅	200	200	200	200	200	300	300	300
GAS Inlet	∅	3/4"	3/4"	3/4"	3/4"	3/4"	1 1/4"	1 1/4"	1 1/4"
STEAM inlet	∅	1"	1"	1"	1"	1"	1 1/4"	1 1/2"	1 1/2"
STEAM outlet	∅	1"	1"	1"	1"	1"	1"	1 1/4"	1 1/4"

DIMENSIONS

Front width	mm	785	785	890	985	985	1270	1270	1270
Depth	mm	840	1100	1245	1054	1210	1085	1345	1577
Height	mm	1694	1694	1812	1946	1946	2380	2380	2380
Net weight	Kg	172	187	210	230	260	395	529	657

DIMENSIONS WITH PACKAGE

Front width	mm	870	870	975	1050	1050	1330	1330	1330
Depth	mm	935	1205	1335	1150	1305	1185	1445	1677
Height	mm	1865	1865	1982	2116	2116	2085	2085	2085
Gross weight	Kg	180	200	230	260	285	430	575	715
Volume	mt ³	1,5	1,95	2,57	2,55	2,9	3,28	4	4,65