

Series: LBS - MP

		LBS 16	LBS 22	LBS 33	LBS 50	LBS 66	LBS 100
DRUM							
Loading capacity ratio 1:10	Kg	16	22	33	50	66	100
Volume of the drum	Lt	158	220	329	489	667	1000
Diameter of the drum	Ø	633	633	800	800	800	1180
Drum lenght	mm	500	700	654	974	1347	1032
Number of drum compartments	Nr	1	1	1	1	2	2
Loading door opening	mm	400x310	400x310	400x310	450x310	450x310	500x900
Height of loading	mm	670	670	750	750	750	960
Basket material	Inox	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L
Drum material	Inox	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L	Aisi 304L
Washing speed	rpm	50	50	50	50	50	50
Extract speed	rpm	1000	1000	1000	900	900	750
"G" factor		361	361	440	360	360	300
Dissipated heat	Kw	1,8	1,8	3,1	4,15	5,05	8
Noise level	Db	65	65	65	65	65	65

ELECTRICAL HEATING

Total installed electrical power	Kw	12	18	27	36	45	75
Electrical consumption	Kw/h	9,6	13	12,4	16,6	20,2	36

STEAM HEATING

Total power	Kw	2,2	2,2	4	5,5	5,5	15
Required steam pressure	Bar	2 ÷ 5	2 ÷ 5	6 ÷ 10	6 ÷ 10	6 ÷ 10	6 ÷ 10
Steam consumption	Kg/h	16,5	16,5	26	40	60	70

ELECTRICAL POWER

Motor	Kw	2,2	2,2	4	5,5	7,5	15
Electrical Heaters	Kw	12	18	27	36	45	75
Total power ELECTRICAL version	Kw	14,2	20,2	31	41,5	52,5	90
Total power STEAM version	Kw	2,2	2,2	4	5,5	7,5	15
HOT WATER version	Kw	2,2	2,2	4	5,5	7,5	15

CONNECTIONS

water outlet	Ø	3"	3"	3"	3"	3"	3"
water inlet	Ø	3/4"	3/4"	3/4"	1"	1"	1"
water pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam inlet	Ø	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"

DIMENSIONS OF THE MACHINE

Front width	mm	980	1180	1276	1596	1949	1680
Depth	mm	910	910	1056	1056	1056	1345
Height	mm	1400	1400	1580	1660	1660	2000
Net weight	Kg	438	471	748	1056	1233	1800

DIMENSIONS WITH PACKAGE

Front width	mm	1072	1262	1452	1752	2102	1800
Depth	mm	1102	1102	1222	1222	1222	1500
Height	mm	1394	1394	1694	1694	1694	2100
Gross weight	Kg	459	494	780	1090	1275	1950
Volume	mt3	1,65	1,94	3,01	3,63	4,35	5,67