

Serie: LRC

		LRC 40	LRC 55	LRC 70	LRC 85
DRUM					
Loading capacity ratio 1:10	Kg	40	50	70	85
Volume of the drum	Lt	395	552	699	848
Diameter of the drum	Ø	880	1080	1200	1200
Drum depth	mm	560	603	618	750
Washing speed	G/min	32	43	26	26
Extract speed	G/min	450	408	355	355
G Factor		100	100	85	85
Noise level	Db	60	60	60	60

LOADING DOOR

Height at the middle of the door	mm	750	750	1087	1119
Diameter of the loading door	Ø	560	560	560	560

ELECTRICAL POWER

Motor	Kw	4	9	10	12
Electrical heaters	Kw	28	30	30	30
Total power of electrical version	Kw	32	39	36	42
Total power of steam version	Kw	4	9	10	12
Total power hot WATER version	Kw	4	9	10	12

CONNECTIONS

Water outlet	Ø	2"	3"	3"	3"
Water inlet	Ø	3/4"	1 1/4"	1 1/4"	1 1/4"
Water pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam inlet	Ø	3/4"	3/4"	3/4"	3/4"

DIMENSIONS OF THE MACHINE

front width	mm	1186	1430	1430	1560
Depth	mm	1186	1410	1572	1563
Height	mm	1565	1875	1875	1870
Net weight	Kg	600	878	1100	1900

DIMENSIONS WITH PACKAGE

Front width	mm	1300	1540	1540	1700
Depth	mm	1300	1500	1540	1650
Height	mm	1880	2020	2020	2200
Gross weight	Kg	630	925	1150	1960
Volume	mt3	3,18	4,66	4,8	6,1