

## Serie: MAQ2 A - TC

		A 11	A14	A18	A25	A35	A45	A60	A120
<b>DRUM</b>									
Loading capacity ratio 1:10	Kg	10	13	18	25	35	45	60	120
Volume of the drum	Lt	100	130	180	250	350	450	600	1200
Diameter of the drum	∅	532	620	700	770	860	918	1048	1360
Drum depth	mm	425	430	470	530	602	720	684	840
Washing speed	G/min	50	50	47	45	42,5	42,5	38	34
Extract speed	G/min	1245	1150	1080	1035	975	850	760	680
G Factor		450	450	450	450	450	350	350	350
Noise level	Db	60	60	60	60	60	60	60	60

### LOADING DOOR

High at the middle of the door	mm	625	700	750	865	885	1118	1118	1330
Diameter of the loading door	∅	290	373	373	373	560	560	560	700

### ELECTRICAL POWER

Motor	Kw	0,75	1,5	2,2	3	4	7,5	11	15
Electrical heaters	Kw	6	9	12	18	21	28,8	36	-----
Total power of electrical version	Kw	6,25	9,5	12,75	19	22	31,3	40	-----
Total power of steam version	Kw	0,75	1,5	2,2	3	4	7,5	11	15
Total power hot WATER version	Kw	0,75	1,5	2,2	3	4	7,5	11	15

### CONNECTIONS

Water outlet	∅	3"	3"	3"	3"	3"	3"	3"	4"
Water inlet	∅	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1 1/2"
Water pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam inlet	∅	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"	1 1/4"

### DIMENSIONS OF THE MACHINE

front width	mm	692	788	884	979	1095	1478	1478	1836
Depth	mm	788	870	914	1041	1184	1444	1444	1863
High	mm	1158	1301	1409	1548	1598	1905	1905	2245
Net weight	Kg	230	250	360	490	750	1350	1400	3950

### DIMENSIONS WITH PACKAGE

Front width	mm	730	830	930	1040	1165	1540	1540	1900
Depth	mm	1000	1010	1030	1160	1230	1580	1580	1940
High	mm	1410	1560	1700	1850	1920	1970	1970	2290
Gross weight	Kg	239	283	393	545	820	1420	1520	4100
Volume	mt3	1,03	1,31	1,63	2,23	2,75	4,79	4,79	8,44