

Series: MAQ2 B - TC

		B 11	B 14	B 18	B 25	B 35	B 60
DRUM							
Loading capacity ratio 1:10	Kg	10	13	18	25	35	60
Volume of the drum	Lt	100	130	180	250	350	600
Diameter of the drum	∅	620	620	700	770	860	1048
Drum depth	mm	330	430	470	530	602	684
Washing speed	G/min	53	53	50	48	45	42,5
Extract speed	G/min	538	538	507	483	458	416
"G" Factor		100	100	100	100	100	100
Noise level	Db	60	60	60	60	60	60

LOADING DOOR

High at the middle of the door	mm	570	570	655	700	735	900
Diameter of the loading door	∅	373	373	373	373	560	560

ELECTRICAL POWER

Motor	Kw	0,75	1	1,5	2,2	3	5,5
Electrical heaters	Kw	6	9	12	18	21	28,8
Total power of electrical version	Kw	6,25	9,3	12,5	18,75	22	31,3
Total power of steam version	Kw	0,75	1	1,5	2,2	3	5,5
Total power hot WATER version	Kw	0,75	1	1,5	2,2	3	5,5

CONNECTIONS

Water outlet	∅	3"	3"	3"	3"	3"	3"
Water inlet	∅	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Water pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam inlet	∅	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"

DIMENSIONS OF THE MACHINE

front width	mm	719	719	788	884	979	1225
Depth	mm	665	810	828	965	1066	1280
High	mm	1158	1158	1308	1318	1408	1640
Net weight	Kg	217	239	281	340	473	930

DIMENSIONS WITH PACKAGE

Front width	mm	800	800	860	930	1050	1360
Depth	mm	990	990	1010	1180	1250	1460
High	mm	1350	1350	1500	1560	1600	1880
Gross weight	Kg	225	247	301	370	503	1050
Volume	mt3	1,07	1,07	1,3	1,7	2,1	3,7